

SPECIALS

Deep Brushed


Specials Aubisque

1204355

190 x 19 cm
15/4 mm

CE
EN 14342-05

25 years
Solidfloor™
guarantee



Packaging

Boards per pack:	8 boards
m ² per pack:	2,89 m ²
Weight per pack:	24 kg
Broken lengths per pack:	25% minimal 60 cm length

Dimensions

Length:	190 cm
Width:	19 cm
Thickness (total):	15 mm
Top layer:	3,5-4,0 mm

Dimensional tolerances according to EN13489

Length:	0,20%
Width:	0,2 mm
Thickness:	Total: 15 mm ± 0,2 mm
Top layer:	3,5-4,0 mm
Height difference between the panels:	≤0,2 mm
Squareness:	≤0,2% across the width
Cup:	≤0,2% across the width
Spring:	≤0,1% over the length
Bend:	≤1% over the length

Other Specifications

Formaldehyde emission:	E1
Insulation value:	R=0,115m ² k/w
Brinell hardness:	Average HB 3.7

Additional specifications

Bevel:	Rounded
Construction:	3-layerd
Moisture content:	7% +/- 2%
Locking system:	Tongue and groove

Instructions and Maintenance

Oil immediately after installation.
Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).



EN 14342-05