

SPECIALS

Herringbone



Packaging

Boards per pack: m² per pack: Weight per pack: Broken lenghts per pack:

Dimensions

Length: Width: Thickness (total): Top layer: 61 cm 12,2 cm 14 mm 2,5-3,0 mm

12 boards

Not allowed

0,893 m²

9 kg

Dimensional tolerances according to EN13489

Length:	0,10%
Width:	0,2 mm
Thickness:	Total: 14 mm ± 0,2 mm
Top layer:	2,5-3,0 mm
Height difference between the panels	: ≤0,2 mm
Squareness:	≤0.2% across the width
Cup:	≤0.2% across the width
Spring:	≤0.1% over the length
Bend:	≤1% over the length

Other Specifications

Formaldehyde emission: Insulation value: Brinell hardness:

Additional specifications

Bevel: Construction: Moisture content: Locking system:

Instructions and Maintenance

Does not need to be oiled after installation. Maintain with Solidfloor™ Ultimate Hardwax Natural & Solidfloor™ Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).

E1

R=0,115m2 k/w

Average HB 3.7

1 mm 4-sided

Tongue and groove

Plywood

, 7% +/- 2%

