

# SPECIALS

Herringbone



**Packaging** 

Boards per pack: 12 boards m² per pack: 0,893 m² Weight per pack: 9 kg
Broken lenghts per pack: Not allowed

#### **Dimensions**

 Length:
 61 cm

 Width:
 12,2 cm

 Thickness (total):
 14 mm

 Top layer:
 2,5-3,0 mm

## Dimensional tolerances according to EN13489

Length: 0,10% Width: 0,2 mm

Thickness: Total: 14 mm  $\pm$  0,2 mm

Top layer: 2,5-3,0 mm Height difference between the panels: ≤0,2 mm

Squareness:≤0.2% across the widthCup:≤0.2% across the widthSpring:≤0.1% over the lengthBend:≤1% over the length

## Other Specifications

Formaldehyde emission: E1
Insulation value: R=0,115m2 k/w
Brinell hardness: Average HB 3.7

### Additional specifications

Bevel: 1 mm 4-sided
Construction: Plywood
Moisture content: 7% +/- 2%
Locking system: Tongue and groove

#### Instructions and Maintenance

Does not need to be oiled after installation.

Maintain with Solidfloor<sup>TM</sup> Ultimate Hardwax Natural & Solidfloor<sup>TM</sup> Woodcleaner. Suitable for underfloor heating & cooling (visit www.solidfloor.com for more information).







